



RICH CONTROL OPTIONS FOR NETWORK CONTROLLER

Our flexible, adaptive architecture gives you options. In addition to the Cloud or On-Premises capabilities, Cambium Networks now offers the option of converting a cnPilot AP into a controller. With this feature, the AP still performs all Wi-Fi functions, enabling you to set your network on *autoPilot*.

cnPilot™ Cloud-Managed Wi-Fi

SCALABLE END-TO-END 802.11ac WAVE 2 and 802.11n WI-FI SOLUTIONS.

For more information go to: cambiumnetworks.com



Frictionless Wi-Fi Everywhere

High-performance Cloud-managed 802.11ac Wave 2 Wi-Fi solutions

Frictionless, adaptive cnPilot Wi-Fi combines high-capacity performance and affordability in one package for rapid roll out of large scale controller-managed Wi-Fi networks for education, hospitality, public Wi-Fi, high density events, small - medium businesses (SMBs), or across any space requiring reliable, affordable Wi-Fi.



cnPILOT INDOOR

High Performance Enterprise

Affordable enterprise-grade high-density 802.11ac Wave 2 indoor access points for schools, indoor public spaces, malls, hotels and resorts, coffee shops, multi-dwelling units (MDUs), or just about any place indoors that needs reliable, high-performance indoor Wi-Fi.



cnPilot e600

Model	Standard	Frequency	SSID	Max Users	Radio
cnPilot e600 Indoor	802.11ac wave 2	Dual Band 2.4 GHz & 5 GHz	16	512	4x4 MU-MIMO
cnPilot e410 Indoor	802.11ac wave 2	Dual Band 2.4 GHz & 5 GHz	16	256	2x2 MU-MIMO
cnPilot e400 Indoor	802.11ac	Dual Band 2.4 GHz & 5 GHz	16	256	2x2 MIMO



cnPILOT OUTDOOR

Meeting the Demand

Controller-managed, Gigabit IP67 802.11ac outdoor access points for enterprise campuses, public Wi-Fi, hospitality, educational institutions, industrial campuses or for just about any demanding outdoor Wi-Fi deployments.

The e500 and e501 APs can be backhauled over Gigabit Ethernet for fiber or copper networks or can mesh with other e-series APs, or can be paired with Cambium's backhaul to rapidly deploy outdoor Wi-Fi.



e500, e501S, e502S

Model	Standard	Frequency	SSID	Max Users	MIMO	IP Rating
cnPilot e500 Outdoor	802.11ac	Omni Dual Band 2.4 GHz & 5 GHz	16	256	2x2	IP67
cnPilot e501S Outdoor	802.11ac	120° Sector Dual Band 2.4 GHz & 5 GHz	16	256	2x2	IP67
cnPilot e502S Outdoor	802.11ac	30° Sector Dual Band 2.4 GHz & 5 GHz	16	256	2x2	IP67
cnPilot e700 Outdoor	802.11ac Wave 2	Omni Dual Band 2.4 GHz & 5 GHz	16	512	2x2 at 2.4 GHz 4x4 at 5 GHz	IP67



cnPII OT e430W WALL PLATE

Enterprise 802.11ac Wave 2 Wall Plate

The cnPilot™ e430W Enterprise class Indoor wall plate access point supporting 802.11ac Wave 2 standards based beamforming, is perfect for hotels, resorts and all hospitality venues, Multi-dwelling units (MDUs) or just about any place indoor that needs a discrete wall mounted AP with multiple Gig E ports to drive Indoor Wi-Fi and wired port network access managed via portals.



cnPilot e430W Wall Plate

Model	Standard	Frequency	SSID	Max Users	MIMO
cnPilot e430W Wall Plate	802.11ac Wave 2	Dual Band 2.4 GHz & 5 GHz	16	256	2x2



cnMAESTRO™

Managing it All

cnMaestro is the cnPilot controller and network management system. The cnMaestro suite of software offers inventory tracking, onboarding of devices, and ongoing daily operations and maintenance including software upgrade, configuration management, statistics monitoring as well as alarms.

cnMaestro is available in the Cloud or as an On-Premises (NOC) virtual software that can be run in a private data center on a local server.



cnMaestro



cnPILOT HOME & SMALL BUSINESS

Simplifying in-home Wi-Fi

Cloud-controlled cnPilot r190W, r200, r201 and r190 routers simplify ISP roll out of indoor home Wi-Fi. The router incorporates 3 additional functions in one package: Wi-Fi, an ATA to connect telephone and fax, and PoE out for powering up Cambium's CPEs (subscriber modules).

Remote secure management via cnMaestro controller features monitoring, configuration management, and integrated troubleshooting across Wi-Fi, client devices and Cambium backhaul (when present), reducing the total cost of network ownership (TCO).



cnPilot R190W

Model	Standard	Frequency	SSID	Max Users	ATA for Voice	Cambium PoE out
cnPilot r190W	802.11n	Single Band 2.4 GHz	4	64		
cnPilot r200, r190V	802.11n	Single Band 2.4 GHz	4	64	Yes	
cnPilot r200P	802.11n	Single Band 2.4 GHz	4	64	Yes	Yes
cnPilot r201	802.11ac	Dual Band 2.4 GHz & 5 GHz	4	128	Yes	
cnPilot r201P	802.11ac	Dual Band 2.4 GHz & 5 GHz	4	128	Yes	Yes
cnPilot r201W	802.11ac	Dual Band 2.4 GHz & 5 GHz	4	128		Yes